



**General Notes:**

1. Expansion joints to be spaced a maximum of 100 feet apart and align with ramps, inlets and other required target points.
2. Contraction/construction joints are required and are to be cut into curb every 10 feet.
3. Details shall meet the standards as set forth in the latest version of the Tennessee Department of Transportation Roadway Design Guidelines.
4. The extruded 6" mountable concrete curb is to be used only in special conditions such as low speed low volume local streets and when tying to similar curbs on subdivision streets or in parking lots.
5. Where concrete median pavement is poured behind extruded 6" mountable concrete curb, it may be poured monolithically with the curb.

- ① 1 1/2" ASPHALTIC CONCRETE SURFACE (GRADING E) ITEM NO. 411-01.11
  - ② TACK COAT (RS-2) ITEM NO. 403-01
  - ③ 2" ASPHALTIC CONCRETE BASE (GRADING B) ITEM NO. 307-01.06
  - ④ PRIME COAT (AE-P) ITEM NO. 402-01
  - ⑤ 8" STONE (GRADING D PUG MILL MIX) ITEM NO. 303-01
- ITEM NUMBERS ARE TO MEET TDOT SPECIFICATIONS



CITY OF  
**COLUMBIA**  
TENNESSEE

**MOUNTABLE CURB DETAIL**

(NTS)

DATE  
4-23-2012

DWG. NO.  
**SD-09**